

5           **ELECTRICAL CABLE HAVING A HARDGRADE-EPR INSULATION****FIELD OF THE INVENTION**

10   The invention relates to an electrical cable having at least one wire including a conductor and an insulation. The insulation surrounds said conductor and comprises at least two insulation layers. Furthermore, the invention also relates to a method for making such an electrical cable.

15   In particular the invention addresses the problem of making an electrical cable which is lightweight, cost effective and which can still fulfill certain properties when exposed to a burn test where the electrical cable is exposed to a very  
20   high temperature under operation. In particular, the insulation should be lightweight and cost effective and should form hard ashes when exposed to the burn test in order to maintain good insulation properties during a high temperature at least over a predetermined period of time.

25   The electrical cable according to the invention can be used as a power transmission cable or a communication transmission cable depending on the purpose of use.

30   **BACKGROUND OF THE INVENTION**

When making an electrical cable having at least one wire including a conductor and an insulation surrounding said conductor and when combining said wires to a cable it is very  
35   important to make sure that the insulation fulfills certain mechanical and electrical properties. For example, the insulation materials need to be selected such that environmental influences like very low or very high

5 temperatures or humidity do not change the insulation properties to such an extent that a short circuit would arise.

Furthermore, in buildings or installations where increased  
10 safety requirements must be satisfied the cables must be fire-resistant. Every country has established certain industrial standards which must be fulfilled by such cables in this respect. For example, according to the German Industrial Standard (DIN Deutsche Industrie-Norm) 4102  
15 Section 12 cables and wires must sustain temperatures up to 1000°C over a period of up to 90 minutes according to a unit temperature time curve. During this time a voltage of 400 Volt is applied to the cables and wires and the cables and wires only pass this burn test if no short circuit or  
20 conductor interruption occurs.

#### DESCRIPTION OF THE PRIOR ART

In order to provide cables and wires with appropriate  
25 insulation properties conventionally conductors have been provided with a double insulation consisting of at least two insulation layers. As shown in Fig. 1, a conductor 7 is surrounded by a first insulation layer 8 and a second insulation layer 9. Typically the first insulation layer 8  
30 consists of a mica tape which is wound on said conductor 7. the second insulation layer 9 may consist of EPR (ethylene-propylene-rubber). If it is, for example, required that the wire continues an operation over 30 minutes or longer when subjected to the burn test, this will require an insulation  
35 thickness of a wire with a cross-section of 1.5 mm<sup>2</sup> including a mica tape to be 1.15 mm (thickness of the mica tape 0.15 mm + thickness of the EPR-insulation 1.0 mm). Since a large insulation thickness is required and since mica tape is quite

5 an expensive material this type of cable is comparatively heavy and expensive. For example, if such type of cables are supplied in great length, e.g. on a spool, then the comparatively large insulation thickness will limit the length that can be supplied on the spool. On the other hand, 10 if the cables are heavy then e.g. the masts needed for holding cables during land line operation need to be very stable and therefore the installation costs also rise.

Another type of a cable K is shown in Fig. 2 and also 15 comprises a double insulation arrangement consisting of a first insulation 8' and a second insulation layer 9. Both insulation layers 8', 9 comprise EPR or a silicone rubber compound. Some cables having the construction of Fig. 2 also comprise silicate or even mica as part of the silicone rubber 20 compound. This type of insulation is thicker than the one shown in Fig. 1 and is also cost intensive.

Finally there are also known cables K according to Fig. 3 where the conductor 7 is surrounded by a single layer 25 insulation consisting of hardgrade-EPR. Hardgrade-EPR is a material which has only recently attracted attention and the properties of hardgrade-EPR have been standardized regarding insulation properties, strength etc. For example, the mechanical and electrical properties of hardgrade EPR are 30 defined in IEC 60502.

Furthermore, it may be noted that the mica tape is very cost intensive and it also requires a complicated manufacturing process since the mica tape has to be spun (wound) on the 35 conductor.

Fig. 4, 5 show conventional constructions of cables comprising a plurality of cores each having core construction

- 5 according to Fig. 1, 2. In Fig. 4 the wires are embedded in a  
common inner sheath 10 which is preferably a fire resistant  
and halogen free component. Over the inner sheath 10 there is  
provided a outer sheath coating or cover 11, for example,  
according to DIN VDE 0266. Conductor 7 consists, for example,  
10 of a copper conductor according to DIN VDE 0295 Class 1 or 2,  
the mica tape consists, for example, of phlogopit and the  
insulation 9 is a rubber mixture on the basis of EPR  
according to DIN VDE 0207 E Section 23 mixture type H11.
- 15 In Fig. 5 a further concentric conductor 12 is provided under  
the outer sheath 11 and over the common inner sheath 10. The  
concentric conductor 11 comprises copper filaments including  
a copper transverse helix.
- 20 Constructions as in Fig. 4, 5 are also possible for the core  
construction shown in Fig. 3

#### PUBLISHED PRIOR ART

- 25 G 91 16 636.5 describes the burn test for cables according to  
DIN 4102, Section 12. The fire resistant electrical cable  
comprises two mica tapes wherein a thin layer of a high  
temperature resistant hard ash forming silicone rubber  
adhesive is arranged between said two mica tapes.
- 30 G 89 02 1116.6 describes a medium voltage or high voltage  
cable comprising a bandage made of a mica paper band  
impregnated with silicone resin. An outer conducting layer is  
also surrounded by a bandage consisting of bands made of  
35 mica.

DE 31 379 56 C2 concerns a fire resistant electrical cable  
having an insulation on a conductor which consists of a

5 polyvinylchloride-mixture. The conductor can also be  
surrounded by a common layer of silicone rubber. It is  
described here that at high temperatures the silicone rubber  
disintegrates and forms powder ashes through which an outer  
metal layer is held together. The metal layer is a kind of  
10 pipe that holds together the ashes in the burn tests.

DE 29 151 88 C2 describes an electrical cable having an  
insulation consisting of cross-linked polyethylene.

15 DE 20 51 192 describes a fire resistant electrical cable  
having an insulation layer and/or an outer layer consisting  
of magnesium carbonate, chloride and antimon trioxide. The  
basic component is polyvinylchloride. Several mixtures for  
the insulation layers are analyzed such as PVC-softeners,  
20 stabilizing agents, lubrication means and calcinated kaolin.  
In particular, ethylene-propylene-rubber (EPR) is used. Only  
a single insulation layer is mentioned and investigated.

DE 26 59 5415 describes an electrical cable having an  
25 insulation made of silicone rubber. A stripe of a  
polymer/metal-laminate is formed on a conductor and a fire  
resistant polymer mixture is extruded as outer layer on the  
surface of said laminate. Therefore, here a double insulation  
is used.

30

DE 39 07 341 A1 describes an insulation layer consisting of a  
mixture of minerals, e.g. silicate or mica. The insulation  
layer also consists of a binding agent which at least over a  
predetermined time does not melt in a burn test. An EPR layer  
35 is extruded on the mica tape similarly as in the above  
described Fig. 1. Furthermore, such type of cable is also  
disclosed in DE 28 10 986.6.

- 5 DE 41 32 390 A1 describes an electrical cable having two layers of mica and an outer insulation of an extruded polymer. Furthermore, a high temperature resistant hard ash forming silicone rubber adhesive is used.
- 10 DE 44 37 596 A1 describes the use of a hard ash forming silicone rubber fire resistant mixture which contains a silicone compound at least a metal oxide and/or a precursor of said metal oxide and other additives. In particular, it is described that an insulation made of ethylene-propylene-
- 15 diene-terpolymers (EPDM)-rubber is used. A further insulation layer consists of a non-burnable mineral material such as silicate, glass and hard ash forming silicone rubber. Therefore, this document describes a double insulation made of EPDM and silicate.
- 20 DE 28 00 688 C2 describes the use of an EPR-rubber as an outer coating for a cable.
- DE 32 28 119 A1 describes a fire resistant cable having
- 25 conductor insulations consisting of thermal plastic halide free fire resistant polymer mixtures. Over the conductor insulation a foil of glimmer paper is applied.

#### SUMMARY OF THE INVENTION

- 30 As explained above, several types of single or double insulation constructions have been used for insulating the core conductor in cable constructions. However, these insulations consist of mica and EPR or EPDM insulations and
- 35 therefore are heavyweight and cost intensive due to the large thickness of insulation required.

5 The present invention aims at avoiding these disadvantages of the prior art. In particular, the object of the present invention is to provide an electrical cable and a manufacturing method therefore such that the electrical cable is lightweight and cost effective.

10

This object is solved by an electrical cable (claim 1) having at least one core including a conductor and an insulation surrounding said conductor and comprising at least two insulation layers, characterized in that wherein a first one  
15 of said layers comprises a silicone rubber compound and a second one of said layers comprises an ethylene(C<sub>2</sub>)-alkylene(C<sub>x</sub>)-copolymer or terpolymer mixture adapted to have properties corresponding to those of a hardgrade-ethylene-propylene-rubber (H-EPR).

20

Furthermore, this object is solved by a method (claim 17) for making an electrical cable, comprising the following steps: providing a conductor; forming an insulation comprising at least a first insulation layer and a second insulation layer  
25 on said conductor; wherein in said step b) a silicone rubber compound layer is formed as said first insulation layer; in said step b) a layer of an ethylene(C<sub>2</sub>)- alkylene(C<sub>x</sub>)-copolymer or terpolymer mixture is formed as said second insulation layer; wherein said ethylene(C<sub>2</sub>)- alkylene(C<sub>x</sub>)-  
30 copolymer or terpolymer mixture is provided to have properties corresponding to those of a hardgrade-ethylene-propylene-rubber (H-EPR).

According to the invention, one of the two layers provided on  
35 the conductor does not comprise EPR or EPDM as explained above, but it includes an ethylene-alkylene-copolymer or terpolymer mixture which has properties corresponding to those of hardgrade-ethylene-propylene-rubber (hardgrade-EPR).

5 Whilst according to the invention a preferred material is  
hardgrade-EPR, the invention comprises one insulation layer  
which consists in general of an ethylene-alkylene-copolymer  
or terpolymer mixture whose mixing ratio has been adapted  
such that the corresponding properties of hardgrade-EPR are  
10 achieved. The properties which are achieved are the defined  
properties regarding the insulation properties and electrical  
properties.

Preferably (claim 4), the second layer can comprise an  
15 ethylene-propylene-copolymer or terpolymer mixture, an  
ethylene-hexene-copolymer or terpolymer mixture or an  
ethylene-octene-copolymer or terpolymer mixture.

Preferably (claim 5), the first layer is arranged on said  
20 conductor and said second layer made of the ethylene-  
alkylene-copolymer or terpolymer mixture is arranged on said  
first layer. However, a different cable construction (claim  
6) may preferably comprise the second layer on the conductor  
1 and the first layer on the second layer.

25 Preferably (claim 3), the silicone rubber compound comprises  
a hard ash forming silicone rubber used for the first layer.  
Such a silicone compound (claim 10) preferably forms hard  
ashes during a burn test process.

30 Preferably (claim 9), the electrical cable constructions  
according to the invention have properties which allow the  
cable to conform with the burn test according to the German  
DIN standard Din 4102 Section 12.

35 Preferably (claim 11), the electrical cable can comprise a  
plurality of cores, a sheath surrounding said plurality of  
cores and an outer coating provided on said sheath. It is



5 also possible (claim 12) that a further conductor is provided under said outer sheath. Preferably (claim 13), the further conductor comprises a plurality of copper filaments.

A particularly advantageous use of the inventive electrical  
10 cable (claim 14, 15) is as a communication cable or as a power cable.

Preferably (claim 23), said first layer and said second layer are formed on the conductor by means of an extrusion step.  
15 This considerably facilitates the manufacture of the inventive electrical cable.

Preferably (claim 24), the first and second layer are extruded on the respective conductor simultaneously. This can  
20 substantially reduce the manufacturing time.

Further advantageous embodiments and improvements of the invention are described in the dependent claims. Furthermore, the invention can comprise embodiments which consist of  
25 features which have been described and/or claimed separately in the description and the claims.

Hereinafter, embodiments of the invention will be described with reference to the drawings. It should be noted that the  
30 invention is not limited to these embodiments and that the described embodiments only constitute what the inventors presently conceive as best mode of the invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

35

Fig. 1 shows an electrical cable K having a double insulation comprising a tape;

- 5    Fig. 2    shows an electrical cable having a double  
insulation consisting of EPR;
- Fig. 3    shows an electrical cable having a single  
insulation made of hardgrade-EPR;
- 10    Fig. 4    shows an electrical cable comprising several wires  
embedded in a inner sheath and surrounded by an  
outer sheath;
- 15    Fig. 5    shows an electrical cable according to Fig. 4 with  
an additional conductor layer provided underneath  
the outer sheath;
- 20    Fig. 6    shows the principal construction of the *core* having  
a double insulation according to the invention;
- 25    Fig. 7a   shows the cable construction including a plurality  
of wires according to the invention in a cross-  
sectional view;
- Fig. 7b   shows the cable construction according to Fig. 7a  
in a side-view;
- 30    Fig. 8a   shows an electrical cable comprising a plurality of  
wires according to the invention including an  
additional conductor layer underneath the outer  
sheath;
- 35    Fig. 8b   shows the cable construction of Fig. 8a  
longitudinally.

- 5 It should be noted that in the drawings the same or similar reference numerals denote the same or similar parts and steps throughout.

#### PRINCIPLE OF THE INVENTION

10

Fig. 6 shows the basic construction of the core K according to the invention. The electrical cable according to the invention has at least one core 1, 2, 3 including a conductor 1 and an insulation 2, 3 surrounding said conductor 1 and  
15 comprising at least two insulation layers 2, 3.

According to the invention a first one of said layers, e.g. the layer 2, comprises a silicone rubber compound. According to the invention a second one of the layers 2, 3, e.g. the  
20 layer 3, comprises an ethylene (C<sub>2</sub>)-alkylene (C<sub>x</sub>)-copolymer or terpolymer mixture adapted to have properties corresponding to those of a hardgrade-ethylene-propylene-rubber (H-EPR).

25 As shown in Fig. 6, the basic cable construction according to the invention is the double insulation layer construction as in Fig. 1. However, the materials used for the layers, in particular for the layer 3 are different.

30 In Fig. 6 an embodiment of the invention is shown where the first layer 2 is arranged on said conductor 1 and where said second layer 3 is arranged on said first layer 2. However, it is also possible that the second layer 3 is arranged on said conductor 1 and said first layer 2 is arranged on said second  
35 layer 3.

A preferred material for the silicone rubber compound comprises a hard ash forming silicone rubber. The silicone

5 rubber compound can also have additionally mixed into it mica  
or silica. This provides additional insulation strength in  
the outer layer 3. In particular, the first layer 2 is made  
from a silicone compound which forms hard ashes during a burn  
test process as was explained above. These hard ashes are  
10 insulating and do not fall off the conductor 1 during the  
burn test.

The purpose of the second layer of an ethylene-alkylene-  
copolymer or terpolymer mixture is to fulfill the mechanical  
15 requirements to hardgrade-EPR such that the total insulation  
thickness of e.g. a wire having a cross section of  $1.5 \text{ mm}^2$   
enduring an operation over 30 minute or longer during said  
burn test is only 0.7 mm.

20 Whilst hardgrade-EPR is a preferred mixture of the ethylene-  
alkylene-copolymer or terpolymer mixture also other ethylene-  
alkylene -copolymer or terpolymer mixtures can be used. A  
preferred example comprises  $\text{C}_2$  (ethylene)- $\text{C}_3$  (propylene)-  
copolymer or terpolymer mixture, a  $\text{C}_2$  (ethylene)- $\text{C}_6$  (hexene)-  
25 copolymer or terpolymer mixture or an  $\text{C}_2$  (ethylene)-  $\text{C}_8$   
(octene)-copolymer or terpolymer mixture. Also combinations  
of the aforementioned mixtures are possible.

The mechanical/electrical properties of hardgrade-EPR are for  
30 example defined in IEC 60502. The most important properties  
are repeated here for convenience:

Tensile strength	min 8.5 MPa
Modulus at 150% elongation at break	min 4.5 MPa
35 International Rubber Hardness Degree (IRHD)	min. 80

- 5 As described above, not only hardgrade-EPR itself fulfills these properties, but also a corresponding mixture consisting of  $C_2-C_x$  (e.g.  $x = 3, 6, 8$ ) copolymer or terpolymer.

10 Whilst in the above described example in Fig. 1 the total insulation thickness of the mica tape and of the second EPR-insulation amounts to 1.15 mm, only a total thickness of the double insulation amounting to 0.7 mm is necessary in the invention according to the inventive combination of the first layer 2 consisting of a silicone rubber compound, e.g. a hard  
15 ash forming silicone rubber, and the second layer 3 consisting of a  $C_2-C_x$ -copolymer or terpolymer mixture. Since the total insulation thickness is only 0.7 mm (e.g. 0.3 mm for the first layer 2 consisting of the silicone rubber compound + 0.4 mm of the second  $C_2-C_x$ -copolymer or terpolymer  
20 layer) a number of significant advantages can be achieved. For example, the cross section of a cable comprising 1 to 5 wires having a construction as in Fig. 6 only amounts to 1.5 mm<sup>2</sup> to 300 mm<sup>2</sup>. The total cross section of a cable comprising 6 to 30 wires only amounts to 1.5 mm<sup>2</sup> to 4 mm<sup>2</sup>.  
25

Therefore, the cables K according to the invention are much lighter than previously known cables whilst achieving the desired mechanical and electrical properties. Since less material must be spent the cables K are also more cost  
30 effective than the previously known cables. Furthermore, supporting structures for holding the cables, e.g. on land line power transmission lines, only need to support a smaller weight such that the construction of the supporting structure can be made easier and more cost effective. On the other  
35 hand, another advantage is that when delivering the cable a longer length of cable can be provided on the same spool or a smaller spool can be used for the same length of cable. A

5 number of other significant advantages are obvious to the skilled person on the basis of the teachings herein.

10 Despite the reduction in the insulation thickness the cable according to the invention is capable of sustaining the burn test according to DIN 4102 Section 12 of the German Industrial Standard as explained above. That is, during the burn test of 1000°C over a period from 30-90 minutes the cable could maintain its operation without forming a short circuit. During the burn test the silicone compound (e.g., the  
15 hard ash forming silicone rubber) forms hard ashes which are held together such that the insulation is maintained whilst the hardgrade-EPR still protects the hard ashes as a kind of pipe. Despite the reduction of wall thickness the same operation properties and insulation properties can therefore  
20 be achieved.

Preferably, all materials used in the layers 2, 3 in Fig. 6 are free of halogene such that during the burn test or any burning of the cable no hydrochloric acid (HCL) is formed.  
25

#### FIRST EMBODIMENT

Whilst Fig. 1 shows the basic core construction only having one core consisting of the conductor 1 and two insulation  
30 layers 2, 3, a number of advantageous embodiments of cable constructions can be provided by the skilled person.

Fig. 7a shows the first embodiment of a cable construction comprising a plurality of cores each having a construction as shown in Fig. 6. A sheath 4 surrounds said plurality of cores  
35 and an outer sheath 5 is provided on said sheath 4. Fig. 7b shows a longitudinal view of the cable construction in Fig. 7a. Since the individual cores have a smaller total diameter

5 due to the usage of the inventive double insulation, a greater number of cores can be arranged in the sheath 5 when it has the same diameter as the construction in Fig. 4 or using the same number of cores the total diameter of the cable K can be reduced.

10

### SECOND EMBODIMENT

Fig. 8a shows a second embodiment of a cable K comprising cores constructions as shown in Fig. 6. Here, a further  
15 conductor 5 is provided underneath said outer sheath 6. Said further conductor can comprise a plurality of spiral copper wires. Fig. 8b shows a longitudinal view of the cable construction K shown in cross-section in Fig. 8a.

20 The conductor 1 can be a copper conductor according to DIN VDE 0295 class 1 or 2. The sheath 6 can be a halogene free fire resistant mixture according to DIN VDE 0266.

Whilst Fig. 7 and Fig. 8 only show preferred examples of  
25 cable constructions according to the invention, the skilled person can derive other cable constructions including wires having the basic construction as in Fig. 6 on the basis of the teachings contained herein.

### 30 THIRD EMBODIMENT

As explained above, according to the invention the cores of the inventive cable K consist of the conductor and the double insulation layer. When such an electrical cable K is  
35 manufactured, the conductor 1 is provided, a first insulation layer 2 consisting of the silicone rubber compound is provided on the layer 1 and the second layer 3 of C<sub>2</sub>-C<sub>x</sub>-copolymer or terpolymer mixture is formed on said first layer

5 2 wherein the C<sub>2</sub>-C<sub>x</sub>-copolymer or terpolymer mixture is prepared beforehand to have properties corresponding to those of a hardgrade-ethylene-propylene-rubber.

Independent as to whether the second layer 3 is formed on  
10 said conductor and said first layer 2 on said second layer or said first layer 2 is formed on said conductor 1 and said second layer 3 is formed on said first layer 2, it should be noted that the first and second layers 2, 3 are extruded onto the conductor 1.

15 According to a preferred embodiment of the manufacturing method of the invention the first and second layer 2, 3 are extruded on the conductor 1 simultaneously. However, it is also possible to first provide one layer via an extrusion  
20 step and then provide the second layer via an extrusion step.

#### INDUSTRIAL APPLICABILITY

As described above, the electrical cable construction  
25 according to the invention provides major advantages in any installation where the cable is used since it is more cost effective, has lower weight and can still sustain the burn test which in particular required for power transmission cables.

30 However, the electrical cable according to the invention can also be used not only in power transmission lines but also as a communication cable.

35 Furthermore, it should be noted that a skilled person can derive further variations and modifications of the embodiments on the basis of the teachings contained herein. In particular, it should be noted that the above described



5   embodiments are only what the inventors presently conceive as  
best mode of the invention. Furthermore, the invention can  
comprise embodiments which consist of features which have  
been described separately in the description and the claims.  
Therefore, it is intended that all embodiments, variations  
10   and modifications fall within the scope of the attached  
claims.

In the claims, reference numerals only serve clarification  
purposes and do not limit the scope of protection.